

WL250

Clean and refreshing water on demand.

The WL250 delivers on a promise of endless refreshing chilled water for your workplace. It features multistage filtration and ultraviolet light sanitization to reduce bacterial growth and prevent potential biofilm buildup. The business friendly design and guaranteed reliability ensure you have all the quality cold and hot water your employees and guests need.



Advanced Technology

The WL250 has three core technologies:



High Performance Filtration

This model can be configured with four stage reverse osmosis filtration or multistage carbon filtration depending on water conditions. These processes remove water contaminants and chlorine to improve water taste and odor.



In-tank UV

An in-tank ultraviolet light reduces bacterial growth to guarantee fresh clean water.



BioCote® Anti-Microbial Protection

Plastic surfaces surrounding the dispensing area are infused with BioCote®.

*For more information visit www.biocote.com/home-us.

Good for the Earth

Waterlogic coolers have been shown to reduce carbon footprint by up to 72% compared to bottled water coolers.*

Bottleless water coolers reduce plastic bottle contribution to landfills.

The WL250 is ENERGY STAR certified.

ENERGY STAR

*Waterlogic 2014 www.waterlogic.com/benefits/simply-green/carbon-reduction-label



WL250 Features

- Filtered chilled and hot water
- UV technology to reduce bacterial growth
- Tower and countertop models
- · Easy connection to your existing water supply
- Option for drip tray drainage



Speak to a Water Expert

See business card for local distributor or visit www.waterlogic.us





Tested and Certified







Waterlogic International Limited reserves the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo are registered trademarks in countries where the Group operates. Waterlogic International Limited is licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.

		Encore Es
Water Options	Technical Features	
Cold water Hot water	Type available	Tower Countertop
	Tower dimensions	13.75" (W) × 41" (H) × 14.5" (D)
	Counter top dimensions	13.75" (W) x 17.75" (H) x 14.5" (D)
	Compressor	120V/60Hz
	Dispense area height	8.5in
	Weight	Tower: 58 lbs Counter Top: 42 lbs
	Recommended filtration	Countertop: Carbon Block (CBC) 1 micron with lead and cyst reduction Tower: Sediment Block, Carbon Block (CBC), Granular Activated Carbon (GAC)
	Additional features	Mode Indicator Leak Detection *CT only
	Capacity	Hot tank: 1.5 liters Cold tank: 4 liters tower 2 liters counter top
	Water temperatures	Cold: 40°F Hot: 188°F